

LIS009086489B2

(12) United States Patent

(10) Patent No.: US 9,086,489 B2 (45) Date of Patent: Jul. 21, 2015

(54) PERSONAL AND AREA SELF-INDICATING INSTANT RADIATION ALERT DOSIMETER

(75) Inventor: **Gordhabhai N. Patel**, Middlesex, NJ

(US)

(73) Assignee: JP Laboratories, Inc, Middlesex, NJ

(US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35

U.S.C. 154(b) by 623 days.

(21) Appl. No.: 13/371,619

(22) Filed: Feb. 13, 2012

(65) Prior Publication Data

US 2012/0181453 A1 Jul. 19, 2012

Related U.S. Application Data

- (60) Division of application No. 11/930,529, filed on Oct. 31, 2007, now Pat. No. 8,115,182, which is a continuation-in-part of application No. 10/545,796, filed as application No. PCT/US2004/005860 on Feb. 26, 2004, now Pat. No. 7,476,874.
- (60) Provisional application No. 60/450,267, filed on Feb. 27, 2003.
- (51) **Int. Cl. G01T 1/04** (2006.01) **G01T 1/06** (2006.01)
- (52) **U.S. CI.** CPC *G01T 1/04* (2013.01); *G01T 1/06* (2013.01)

(56) References Cited

U.S. PATENT DOCUMENTS

2,680,816 A 6/1954 Stern 2,824,234 A 2/1958 Schulte et al. 3,053,983 A 9/1962 Faulkner et al. 3,290,499 A 12/1966 Lester et al. 3,787,687 A 1/1974 Trumble 7/1975 Cox et al. 3,999,946 A 12/1976 Patel et al. (Continued)

FOREIGN PATENT DOCUMENTS

EP 0 117 390 5/1984 EP 0 325 863 11/1990

OTHER PUBLICATIONS

Gordon K. Reil and Charles Woodruff, Low Cost Self Indicating Dosimeter (LCSID), International Conference on Low-Level Radiaton Injury and Medical Countermeasures, Nov. 8-10, 1999 Bethesda MD.

(Continued)

Primary Examiner — Mark R Gaworecki
(74) Attorney, Agent, or Firm — Barbara V Maurer

(57) ABSTRACT

Described is a self-indicating instant radiation dosimeter (1001) for monitoring high energy radiations, such as X-ray. The dosimeter contains a radiation sensitive, color changing, indicating composition (10), e.g., a diacetylene (R—C—C—C—C—R', where R and R' are substituents groups) or a radiochromic dye, a polymeric binder (20) and optionally a shelf life extender (50) or an activator (40). The radiation sensitive composition (10) changes color instantly when exposed to high energy radiation. The dose is estimated by comparing the color with a color reference chart or more accurately with a spectrophotometer or an optical densitometer. The radiation sensitive composition (10) is protected from low energy radiation such as UV light, by a layer of low energy absorbing materials, such as UV absorbers.

5 Claims, 16 Drawing Sheets

